Acknowledged globally



VAMP-U

Item Number 3004309

Condensate pump for direct installation below the air conditioning unit
The VAMP-U is the condensate pump in the VAMP series designed for direct installation below the air conditioning unit. It is installed outside the unit and requires no space inside the air conditioning unit or duct.

Thanks to its compact design, the VAMP-U integrates discreetly below the air conditioning unit. Its flexible positioning allows it to be used in a wide range of installation situations.

Quick installation, maximum flexibility
The VAMP-U is mounted directly below the air conditioning unit and is ideal for applications where installation inside the unit or duct is not intended. Fewer components ensure a quick, straightforward installation and easy mounting on site.

Quiet, precise, powerful
With a noise level below 18 dB(A), the VAMP-U operates particularly quietly. Vibration-damping pads support smooth, quiet operation.
The optical sensor ensures precise level measurement and reliable operation.
Proven diaphragm pump technology provides a flow rate of up to 22 litres per hour and a discharge head of up to 15 metres.

- Quick and easy installation with maximum flexibility
- Compact design for discreet installation below the air conditioning unit
- Vibration-damping pads reduce operating noise
- Direct installation below the air conditioning unit – no installation inside the unit or duct required
- Fewer components for quick and straightforward installation
- Quiet operation: below 18 dB(A) thanks to diaphragm pump technology and vibration damping
- Flow rate: up to 22 litres per hour

REFCO Manufacturing Ltd.
Industriestrasse 11
6285 Hitzkirch

Phone +41 41 919 72 82
info@refco.ch

Certificate
ISO 9001 / ISO 14001

- Discharge head: up to 15 metres
- Optical level sensing technology: interference-resistant and precise
- Integrated switching power supply: universal operation with 100–240 VAC
- Sustainability: housing made from plant-based material
- Made in Switzerland

Technical Data

Material	Polyamide | FR-4
Colour	signal white (RAL 9003)
Standards	IEC 60335-1, IEC 60335-2-41, UL 778, CSA C22.2 #108
RoHS Conformity	Yes
Type	Diaphragm type
Operating Temperature Range	3 °C – 40 °C
Storage Temperature Range	-20 °C – 70 °C
Water Temperature Range	3 °C – 40 °C
Frequency	50Hz/60Hz
Protection Class	II
Ingression Protection	IP44
Energy Consumption	6 W
Max. Flow Rate	22 l/h
Max. Suction Lift	2 m
Max. Discharge height	15 m
Noise Level	18 dB(A)
Alarm Relay	Normally-closed, failsafe 250 VAC, 5 A or 30 VDC, 5 A
Tube Diameter	6 mm
Packaging	Cardboard box
Scope of Supply	Condensate pump Installation-Cable Housing (front & back) Water tray with filter 3x Screws 3x Wall plug Anti-Siphon Valve

REFCO Manufacturing Ltd.
Industriestrasse 11
6285 Hitzkirch

Phone +41 41 919 72 82
info@refco.ch

Certificate
ISO 9001 / ISO 14001

	Outlet tube Retaining clip Inline connector Quick guide
Max. Horizontal Run	75 m at 0 m head and 0 m suction
Power Consumption Idle	0.6 W

Accessories

3004186	STAR-TUBE-600	Yellow star tube, 15m / 600 inches
3004087	KIT-4087	Star tube with Siphon device
4679160	PVC-TUBE	Plastic tube 6 mm, 30 meters, 1/4"
3004252	AP-mL/3	Adapter for VAMP condensate pumps, 3 pcs.
3004257	SM-ALL/3	Adapter for VAMP condensate pumps, 3 pcs.
3004253	SCM-FWD/3	Adapter for VAMP condensate pumps, 3 pcs.
4689101	AP-mO/3	Adapter for VAMP condensate pumps, 3 pcs.
4678597	IN-LINE FILTER	Filter for condensate water
3004258	AP-mA/3	Adapter for VAMP condensate pumps, 3 pcs.

Spare Parts

3004238	VAMP-F	Condensate pump with integrated reservoir and optical level sensor. With extendable posable hose for quick installation
3004328	ANTI-SIPHON/4	Replacement high flow anti-siphon, 4 pieces
4689089	CP-INSTALLATION-CABLE	Installation cable for VAMP condensate pumps